

SLIDING DOOR SPECIFICATIONS

- Glazing in windows complies with AS 1288. Human Impact Requirements
- Purchaser to specify if door conditions vary from this
- These products are designed to 1000pa wind pressure and 150pa water pressure
- All frames are viewed from the outside

SLIDING COURTYARD DOORS

STUD OPENING		1830	2420
FRAME		1810	2400
2127 2417	2107		
	2397		
		2725	3620
		2705	3600
2127 2417	2107		
	2397		
		3620	4820
		3600	4800
2127 2417	2107		
	2397		

SLIDING TERRACE DOORS

STUD OPENING		1830	2420
FRAME		1810	2400
2127 2417	2107		
	2397		
		2725	3620
		2705	3600
2127 2417	2107		
	2397		
		3566	4746
		3546	4726
2127 2417	2107		
	2397		

These configurations / sizes are provided as a guide. Homeview can manufacture this product to suit most openings. Timber and aluminium flywire screens are available with this product. Lockable and non-lockable hardware is also available. Options are only available at time of ordering Please note: Some frames may require doors or sashes removed upon delivery and or onsite glazing depending on size



1 Standard 2 Colonial Bar 3 Multi Colonial Bar

1 Standard 2 Colonial Bar 3 Multi Colonial Bar 4 Federation Bar 5 Heritage Bar

Our commitment to continual product development necessitates that sizes and specifications may change without notice.